

View Online at <https://aerobasegroup.com/nsn/5935-00-457-5755>

Body Style:

Straight edge type w/card guide

Overall Length:

3.266 inches

Overall Height:

0.391 inches

Overall Width:

0.688 inches

Unthreaded Mounting Hole Diameter:

0.078 inches

Distance Between Mounting Facility Centers:

2.875 inches

Board Accommodated Length:

2.438 inches single board

Board Accommodated Width:

0.125 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Connector Locking Method:

Friction

End Application:

Over the horizon back scanner (oth-b) program (an/fps-118). Sonar signal processing system an/sqq-2 (v). Teletype model 28. Consolidated space operations center. Spruance class dd (963), emory s. Land class as, wasp class lhd, arleigh burke class ddg, oliver perry class ffg, ticonderoga class cg (47) .

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Metal single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end single contact grouping

Included Contact Quantity:

50 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Weapon system essential

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.050 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.