Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-458-6057

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, flange mount, external threaded ground screw coupling
Overall Height:
1.375 inches
Overall Width:
1.375 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.062 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.062 inches
Distance From Mounting Shoulder To Front Face:
0.750 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
18-1 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
200.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
250.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Potting
Connector Locking Method:
Externally threaded shell



**Connector Cable Strain Relief Method:** Potting type Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.125 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Silver **Included Contact Quantity:** 10 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.010 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0

--