Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-459-0791

### Body Style:

Straight shape

### **Overall Length:**

Between 2.526 inches and 2.556 inches

### **Overall Height:**

0.588 inches

#### **Overall Width:**

Between 0.479 inches and 0.509 inches

### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

### Distance Between Mounting Facility Centers:

Between 1.307 inches and 1.317 inches

### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

"2, 15" single mating end

### **Contact Removability:**

Nonremovable single mating end single contact grouping

### Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

### Polarization Method:

Mating end

### Shell Type:

Solid

## Terminal Location:

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

## Insert Material:

Plastic diallyl phthalate single mating end

# Contact Surface Treatment Specification:

Mil-g-45204, type ii, class 2 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Solder well single mating end single contact grouping

## Shell Material:

Steel

## Shell Surface Treatment:

Cadmium

# Shell Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response



Included Contact Quantity:

15 single mating end single contact grouping

#### Included Contact Type:

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact sufaces gold

### **Precious Material And Weight:**

0.015 gold grains, troy

### **Precious Material:**

Gold

Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.