NSN 5935-00-459-0791

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-459-0791

Body Style: Straight shape **Overall Length:** Between 2.526 inches and 2.556 inches **Overall Height:** 0.588 inches **Overall Width:** Between 0.479 inches and 0.509 inches **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Distance Between Mounting Facility Centers:** Between 1.307 inches and 1.317 inches **Mating End Quantity: Contact Position Arrangement Style:** "2, 15" single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type ii, class 2 military specification single treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Steel

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

NSN 5935-00-459-0791

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 15 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact sufaces gold **Precious Material And Weight:** 0.015 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.