NSN 5935-00-459-4140

Thread Class: 2a and 2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-459-4140

Thread Direction: Right-hand and right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 3.000 inches **Overall Diameter:** Between 1.490 inches and 1.510 inches **Environmental Protection:** Moisture proof and salt water resistant **Distance From Mounting Shoulder To Front Face:** Between 1.490 inches and 1.510 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 302.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 20 and 20 **Thread Size:** 1.000 inches and 1.000 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Nickel alloy single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Steel

NSN 5935-00-459-4140

Electrical Receptacle Connector - Page 2 of 2



Ind	clud	led	Con	tact	Qua	ntity:
	JIUU	ıcu	CULI	ιαυι	wua	HILLLY.

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial pin single mating end single contact grouping

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0