## NSN 5935-00-459-5437

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-459-5437 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Round flange mount, external coupling **Overall Length:** Between 0.892 inches and 0.910 inches **Bushing Diameter:** Between 1.371 inches and 1.375 inches **Mounting Hole Circle Radius:** 1.655 inches **Overall Diameter:** Between 1.803 inches and 1.823 inches **Environmental Protection:** Fungus proof and humidity resistant and salt water resistant **Unthreaded Mounting Hole Diameter:** Between 0.076 inches and 0.080 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 24-28 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1000.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thread Length: 0.625 inches **Thread Size:** 1.500 inches

**Terminal Location:** 

Back single mating end single contact grouping

## NSN 5935-00-459-5437

Electrical Receptacle Connector - Page 2 of 2



insert material:
Plastic single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
24 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0