

View Online at <https://aerobasegroup.com/nsn/5935-00-460-3728>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape w/flange

Overall Length:

1.578 inches

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.718 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.718 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

2

Contact Position Arrangement Style:

C all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1000.0 all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Bayonet pin and friction

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thread Size:

0.112 inches

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Silver 2nd mating end all contact groupings

Insert Material:

Plastic tetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Qq-s-365, type 2, grade a federal specification single treatment response 2nd mating end all contact groupings

Contact Material Specification:

Qq-c-530, comp ht federal specification single material response 1st mating end all contact groupings

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Surface Treatment Specification:

Qq-s-365, type 2, gr a federal specification single treatment response

Shell Material Specification:

Qq-b-626, comp 22, 1/2 h federal specification single material response

Included Contact Quantity:

1 2nd mating end all contact groupings

Included Contact Type:

Coaxial socket 2nd mating end all contact groupings

Precious Material And Location:

Contact surface gold and contact and body surfaces silver

Precious Material And Weight:

0.005 gold grains, troy and 0.105 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.