

View Online at <https://aerobasegroup.com/nsn/5935-00-460-5676>

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.296 inches

**Overall Diameter:**

1.866 inches

**Environmental Protection:**

Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant and humidity resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

61 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

75.0

**Shell Type:**

Solid

**Connector Locking Method:**

Spring friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Rubber silicone class q single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, grade e federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Included Contact Quantity:**

61 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.061 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.