Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-462-3703

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.340 inches
Overall Height:
1.351 inches
Overall Width:
1.351 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.116 inches and 0.126 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.057 inches and 1.067 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.057 inches and 1.067 inches
Distance From Mounting Shoulder To Front Face:
0.775 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
262.0 and 208.0 and 92.0 and 22.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
28
Thread Size:
1.125 inches
Terminal Location:
Back single mating end single contact grouping



Contact Mater	
	ingle mating end single contact grouping
Contact Surfa	
Gold single ma	ting end single contact grouping
Contact Surfa	ce Treatment Specification:
Mil-g-45204, ty	ppe 2, class 1 military specification single treatment response single mating end single contact grouping
Terminal Type	
Crimp single m	nating end single contact grouping
Shell Material:	:
Aluminum alloy	/ 6061
Shell Surface	Treatment:
Chromium	
Shell Material	Specification:
Qq-a-367 feder	ral specification single material response
Included Cont	tact Quantity:
21 single matin	ng end single contact grouping
Included Cont	tact Type:
Round pin sing	le mating end single contact grouping
Precious Mate	erial And Location:
Contact surface	es gold
Precious Mate	erial And Weight:
0.021 gold grai	ins, troy
Precious Mate	erial:
Gold	
Thread Series	Designator:
Un	
Shelf Life:	
N/a	
Unit Of Measu	ire:
Demilitarizatio	on:
No	
Fiig:	
A039b0	
Mil-std (militar	ry Standard):
Mil-g-45204 sp	ec.