Electrical Connector Backshell - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-00-462-6602

2b Thread Direction: Right-hand Overall Langth: 1.030 inches 1.030 inches Develal Langth: 1.030 inches Develal Diameter: Between 0.400 inches and 0.400 inches Cable Opening Diameter: Between 0.400 inches and 0.400 inches Cable Opening Quantity: 1 Size Designation: 10 10 Munting Facility Type And Quantity: 1 threaded coupling Thread Size: 0.303 inches 0.303 inches Size Designation: 0.303 inches Munting Hack Size Centertion: 0.303 inches Outrig Test Size: 0.303 inches Size Designator: Cardinum Strice Testment: Cardinum Strice Testment: Cardinum Strice Testment: Cardinum Thread Size Designator: Cardinum Cardinum Thread Size Designator:		
Thread Direction: Right-hand Overall Length: 1.030 inches Overall Dimeter: Between 1.040 inches and 1.080 inches Cable Opening Diameter: Between 0.450 inches and 0.490 inches Cable Opening Quantity: 1 Size Designation: 1 1 Mounting Facility Type And Quantity: 1 1 Thread Oxyping Thread Vity Per Inch (tpl): 20 Priced Size: 0.938 inches Material: Auminum alloy Surface Treatment: Cadmium Singlit shape solid type Surface Treatment: Cadmium Stright shape solid type Surface Treatment: Cadmium Thread Stries Designator: Ca	Thread Class:	
Right-hand Overall Length: 1.030 inches Overall Diameter: Between 1.040 inches and 1.080 inches Cable Opening Diameter: Between 0.450 inches and 0.490 inches Cable Opening Quantity: 1 Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 0.930 inches Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 0.930 inches Marrial: Aurinum alloy Surface Treatment: Cadmium Size Designator: Size Treatment: Cadmium Thread Size: Cadmium Size Treatment: Cadmium Size Treatment: Cadmium Thread Size: Cadmium Thread Size Designator: Cadmium Thread Size Designator: Cadmium Thread Size Designator: Cadmium Diatize	2b	
Overall Length: 1.030 inches 1.030 inches Overall Diameter: Between 0.400 inches and 0.800 inches Cable Opening Diameter: Between 0.450 inches and 0.490 inches Cable Opening Quantity: 1 Size Designation: 6 Mounting Facility Type And Quantity: 1 1 threaded coupling Thready City Per Inch (tp): 20 Size Designation: 303 inches Material: Aurinum alloy Surface Treatment: Cadmium Straget shape solid type Straget reatment: Cadmium Thread Selignator: Cadmium <td>Thread Direction:</td> <td></td>	Thread Direction:	
1.030 inches Overall Diameter: Between 1.040 inches and 1.080 inches Cable Opening Diameter: Between 0.450 inches and 0.400 inches Cable Opening Quantity: 1 Size Designation: 1 Size Designation: 1 Horeaded coupling Thread Style P Inch (tpl): 20 Thread Style Inch (tpl): 20 Thread Style Designato: 20 Style	Right-hand	
Overall Diameter: Between 1.040 inches and 1.080 inches Cable Opening Diameter: Between 0.450 inches and 0.490 inches Cable Opening Quantity: Cable Opening Quantity: 1 Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Cap Per Inch (tpi): 20 Thread Size: 0.938 inches Material: Auminum alloy Surface Treatment: Cadmium Straight shape solid type Surface Treatment: Cadmium Thread Series Designator: Lined Durild Tote Series Cadmium Straight shape solid type Surface Treatment: Cadmium Thread Series Designator: Lined Surface Treatment: Cadmium Surface Treatment: Cadmium Thread Series Designator: Lined Diff Life: Na Surface Treatment:	Overall Length:	
Between 1.040 inches and 1.080 inches Cable Opening Diameter: Between 0.450 inches and 0.490 inches Cable Opening Quantity: Cable Opening Cable Opening Cable Opening Quantity: Cable Opening Quantity: Cable Opening Cable Opening Cable Opening Cable Opening Cable Opening Quantity: Cable Opening Cable Op	1.030 inches	
Cable Opening Diameter: Between 0.450 inches and 0.490 inches Cable Opening Quantity: 1 Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Privat Size: 0.938 inches Material: Adminum alloy Surface Treatment: Cadmium Style Designator: Strafaght shape solid type Strade Strafaght shape	Overall Diameter:	
Between 0.450 inches and 0.490 inches Cable Opening Quantity: 1 Size Designation: 1 I I I Size Designation: 1 I I I I I I I I I I I I I I I I I I	Between 1.040 inches and 1.080 inches	
Cable Opening Quantity: 1 Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qy Per Inch (tpi): 20 Thread Size: 0.393 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Strates Treatment: Cadmium Strates Treatment: Cadmium Style Designator: Cadmium Unit of Measure: Via Unit of Measure: Cadmium Thread Series Designator: Cadmium Thread Series Designator: Cadmium Thread Series Designator: Cadmium Thread Series Designator:	Cable Opening Diameter:	
1 Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight shape solid type Surface Treatment: Cadmium Style Designator: Straight shape solid type Surface Treatment: Cadmium Thread Series Designator: Unef Did Of Measure: Cadmium Thread Series Designator: Unef Biel Line: Na Did Of Measure: Tore Fig:	Between 0.450 inches and 0.490 inches	
Size Designation: 16 Mounting Facility Type And Quantity: 1 threaded coupling Threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.938 inches Material: 0.938 inches Material: 0.938 inches Material: Auminum alloy Surface Treatment: Cadmium Style Designator: Strlaght shape solid type Surface Treatment: Cadmium Cad	Cable Opening Quantity:	
16 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Strates Treatment: Cadmium Strates Treatment: Cadmium Style Designator: Strates Treatment: Cadmium Thread Series Designator: Curface Treatment: Cadmium Thread Series Designator: Unif Dread Series Designator: Unif Dread Series Designator: Na Duti Of Measure: - Pomilitarization: No Fig:	1	
Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: Na Unif Measure:	Size Designation:	
I thread coupling Thready Qty Per Inch (tpi): 20 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight shape solid type Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No	16	
Thready Quy Per Inch (tpi): 20 Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straface Treatment: Cadmium Style Designator: Cadmium Thread Stries Designator: Chread Stries Designator: Unef Stelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Mounting Facility Type And Quantity:	
20 Tread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Style Designator: Striaght shape solid type Surface Treatment: Cadmium Thread Series Designator: Undf Shelf Life: Na Undf Measure: Denilltarization: No Fig: i	1 threaded coupling	
Thread Size: 0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight shape solid type Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: Na Denilltarization: Tread Series Designator: Unef Shelf Life: Na Dim Of Measure: Demilitarization: Na Fig:	Thready Qty Per Inch (tpi):	
0.938 inches Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight shape solid type Surface Treatment: Cadmium Thread Series Designator: Unef Sheff Life: N/a Unit Of Measure: Demilitarization: No Fije:	20	
Material: Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight shape solid type Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Thread Size:	
Aluminum alloy Surface Treatment: Cadmium Style Designator: Straight shape solid type Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:	0.938 inches	
Surface Treatment: Cadmium Style Designator: Straight shape solid type Surface Treatment: Cadmium Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Material:	
Cadmium Style Designator: Straight shape solid type Sturface Treatment: Cadmium Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Aluminum alloy	
Style Designator: Straight shape solid type Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Surface Treatment:	
Straight shape solid type Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Cadmium	
Surface Treatment: Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No	Style Designator:	
Cadmium Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No	Straight shape solid type	
Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Surface Treatment:	
Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Cadmium	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Thread Series Designator:	
N/a Unit Of Measure: Demilitarization: No Fiig:	Unef	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
	No	
A10100	Fiig:	
	A10100	