

View Online at <https://aerobasegroup.com/nsn/5935-00-463-2558>

**Body Material:**

Plastic

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Top mount w/studs

**Overall Length:**

1.440 inches

**Temperature Rating:**

-65.0 degrees celsius and 125.0 degrees celsius

**Overall Height:**

0.732 inches

**Overall Width:**

0.610 inches

**Mounting Hole Diameter:**

0.112 inches

**Body Mounting Hole Accommodation Length:**

0.980 inches

**Body Mounting Hole Accommodation Width:**

0.610 inches

**Mounting Hole Style:**

Rectangular, w/four mounting holes/slots

**Specific Equipment Accommodated:**

Relay

**Contact Maximum Current Rating In Amps:**

3.0

**Contact Material:**

Copper alloy

**Contact Surface Treatment:**

Gold

**Accommodated Contact Quantity:**

14

**Center To Center Distance Between Outside Mounting Holes Along Length:**

1.200 inches

**Center To Center Distance Between Outside Mounting Holes Along Width:**

0.400 inches

**Polarization Type:**

Colored dot

**Projection Length Below Mounting Surface:**

0.168 inches

**Mounting Method:**

Threaded stud

**Mounting Type For Which Designed:**

Chassis

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.112 inches

**Contact Position Arrangement Style:**

Symmetrical

**Contact Maximum Voltage In Volts And Current Type:**

1400.0 ac and 1400.0 dc

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.014 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Furnished Items And Quantity:**

4 stud and 4 nut and 4 lock washer

**Terminal Type And Quantity:**

14 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02300