

View Online at <https://aerobasegroup.com/nsn/5935-00-463-2558>

Body Material:

Plastic

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Top mount w/studs

Overall Length:

1.440 inches

Temperature Rating:

-65.0 degrees celsius and 125.0 degrees celsius

Overall Height:

0.732 inches

Overall Width:

0.610 inches

Mounting Hole Diameter:

0.112 inches

Body Mounting Hole Accommodation Length:

0.980 inches

Body Mounting Hole Accommodation Width:

0.610 inches

Mounting Hole Style:

Rectangular, w/four mounting holes/slots

Specific Equipment Accommodated:

Relay

Contact Maximum Current Rating In Amps:

3.0

Contact Material:

Copper alloy

Contact Surface Treatment:

Gold

Accommodated Contact Quantity:

14

Center To Center Distance Between Outside Mounting Holes Along Length:

1.200 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

0.400 inches

Polarization Type:

Colored dot

Projection Length Below Mounting Surface:

0.168 inches

Mounting Method:

Threaded stud

Mounting Type For Which Designed:

Chassis

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Contact Position Arrangement Style:

Symmetrical

Contact Maximum Voltage In Volts And Current Type:

1400.0 ac and 1400.0 dc

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.014 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Furnished Items And Quantity:

4 stud and 4 nut and 4 lock washer

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02300