NSN 5935-00-464-8966

Contact Surface Treatment:

Gold single mating end single contact grouping

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-464-8966

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.437 inches
Overall Diameter:
0.312 inches
Environmental Protection:
Humidity resistant and shock resistant and vibration resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Sma single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Connector Cable Strain Relief Method:
Shrinkable tubing
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
End Application:
Fms-aircraft, hawkeye e-2c; radar iff system an/tpx-42 (v); f4s aircraft; communications terminal, satellite an/gsc-39(v)1; missile,
air-to-air, phoenix (aim-54) sturgeon class ssn (637) los angeles class ssn (688) support equipment, mx peacekeeper missile; submarine
armament and fire control systems; aircraft, tomcat f-14
Thread Length:
0.150 inches
Thready Qty Per Inch (tpi):
36
Thread Size:
0.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping

NSN 5935-00-464-8966

Electrical Plug Connector - Page 2 of 2



Insert Material:
Plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204 ty ii, cl 2 military specification single treatment response single mating end single contact grouping
Criticality Code Justification:
Feat
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping
Shell Material:
Steel
Shell Material Specification:
Qq-s-764, cl 303 condition a federal specification single material response
Insert Material Specification:
Mil-p-19468 military specification single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Special Features:
Weapon system essential
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.