NSN 5935-00-465-4030

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-465-4030 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.266 inches **Overall Height:** Between 1.552 inches and 1.573 inches **Overall Width:** Between 1.552 inches and 1.573 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** 0.790 inches **Threaded Device Type:** Back shell and mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 21-39 single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 850.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 18 and 40

Thread Size:

0.312 inches and 0.112 inches

NSN 5935-00-465-4030

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
37 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Special Features:
Furnished items - gasket
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.039 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039h0