NSN 5935-00-465-7895

Contact Surface Treatment Specification:

federal specification 2nd treatment response single mating end all contact groupings

Body Style:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-465-7895

Straight shape, external coupling w/backshell
Overall Length:
1.552 inches
Overall Height:
1.234 inches
Overall Width:
1.234 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.969 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.969 inches
Distance From Mounting Shoulder To Front Face:
0.431 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
16-95 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end 2nd contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and nickel single mating end all contact groupings
Insert Material:
Rubber single mating end

Mil-g-45204, type 1, cl 1, grade c military specification 1st treatment response single mating end all contact groupings and qq-n-290, grade e

NSN 5935-00-465-7895

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Included Contact Quantity:
6 single mating end 2nd contact grouping
Included Contact Type:
Coaxial pin single mating end 1st contact grouping
Precious Material And Weight:
0.018 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.