

View Online at <https://aerobasegroup.com/nsn/5935-00-466-1245>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Electrical Insulation Feature:**

Insulated completely

**Identification Code Color:**

Black

**Body Style:**

Threaded bushing mounted

**Overall Length:**

0.940 inches

**Mounting Bushing Length:**

0.470 inches

**Body Length:**

0.660 inches

**Overall Diameter:**

0.440 inches

**Bushing Accommodation Hole Shape:**

Round w/flat

**Maximum Voltage Rating In Volts:**

10000.0 dc

**Accommodated Finger Type:**

Banana spring single finger

**Finger Accommodation Diameter:**

0.175 inches single finger

**Finger Accommodation Length:**

0.660 inches single finger

**Bushing Thru-hole Accommodation Length:**

0.230 inches

**Bushing Thru-hole Accommodation Width:**

0.328 inches

**Capacitance In Picofarads:**

2.4

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.250 inches

**Terminal Type:**

Tab, solder lug

**Material:**

Plastic, fluorinated ethylene propylene insulator

**Material:**

Plastic fluorinated ethylene propylene insulator

**Surface Treatment:**

Cadmium spring

**Surface Treatment:**

Cadmium spring

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03400