## NSN 5935-00-466-1245

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-466-1245

Thread Class:
2a
Thread Direction:
Right-hand
Electrical Insulation Feature:
Insulated completely
Identification Code Color:
Black
Body Style:
Threaded bushing mounted
Overall Length:
0.940 inches
Mounting Bushing Length:
0.470 inches
Body Length:
0.660 inches
Overall Diameter:
0.440 inches
Bushing Accommodation Hole Shape:
Round w/flat
Maximum Voltage Rating In Volts:
10000.0 dc
Accommodated Finger Type:
Banana spring single finger
Finger Accommodation Diameter:
0.175 inches single finger
Finger Accommodation Length:
0.660 inches single finger
Bushing Thru-hole Accommodation Length:
0.230 inches
Bushing Thru-hole Accommodation Width:
0.328 inches
Capacitance In Picofarads:
2.4
Thready Qty Per Inch (tpi):
32
Thread Size:
0.250 inches
Terminal Type:
Tab, solder lug
Material:
Plastic, fluorinated ethylene propylene insulator

## NSN 5935-00-466-1245

Tip Jack - Page 2 of 2



Material:

Plastic fluorinated ethylene propylene insulator

Surface Treatment:

Cadmium spring

Surface Treatment:

Cadmium spring

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03400