## NSN 5935-00-466-3571

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-466-3571

View Online at https://aerobasegroup.com/nsn/5935-00-466-3571
Body Style:
Straight shape, external coupling w/strain relief
Overall Length:
2.200 inches
Overall Diameter:
1.578 inches
<b>Environmental Protection:</b>
Moisture proof and vibration proof
Cable Entrance Diameter:
0.188 inches
Distance From Mounting Shoulder To Front Face:
0.535 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
22-95 single mating end
Contact Removability:
Removable single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Cable clamp
Terminal Location:
Back single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification 1st treatment response
Included Contact Quantity:

6 single mating end 1st contact grouping

**Included Contact Type:** 

Round socket single mating end all contact groupings

## NSN 5935-00-466-3571

Electrical Receptacle Connector - Page 2 of 2



S	ne	cial	Feature	es:
J	μυ	viai	. catar	<b>5</b> .

Solder flange mounting

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0