## NSN 5935-00-467-1681

Connector Adapter - Page 1 of 2

Straight shape, external/internal coupling

**Thread Class:** 

Right-hand **Body Style:** 

**Thread Direction:** 

Overall Length: 1.234 inches

**Overall Diameter:** 

0.625 inches

2b



View Online at https://aerobasegroup.com/nsn/5935-00-467-1681

Threaded Device Type:
Coupling facility
Mating End Quantity:
2
Contact Position Arrangement Style:
Nonstd 1st mating end
Contact Removability:
Nonremovable all mating ends all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
500.0 all mating ends all contact groupings
Contact Maximum Frequency Rating:
10000.0 megahertz all mating ends all contact groupings
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring and bayonet pin
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 all mating ends all contact groupings
Thread Size:
0.438 inches
Contact Material:
Copper alloy all mating ends all contact groupings
Contact Surface Treatment:
Silver all mating ends all contact groupings
Insert Material:
Rubber all mating ends
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response all mating ends all contact groupings
Contact Material Specification:
Qq-c-530, cond h federal specification single material response all mating ends all contact groupings
Shell Material:
Copper alloy

## **NSN 5935-00-467-1681** Connector Adapter - Page 2 of 2



Shell Surface Treatment:
Silver
Shell Surface Treatment Specification:
Qq-c-530, cond h federal specification single treatment response
Included Contact Quantity:
1 2nd mating end all contact groupings
Special Features:
Contact designation tnc
Precious Material And Location:
Contact and body surfaces silver
Precious Material And Weight:
0.110 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0