Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-468-0938

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.500 inches

Bushing Diameter:

0.250 inches

Overall Height:

0.500 inches

Overall Width:

0.500 inches

Unthreaded Mounting Hole Diameter:

Between 0.100 inches and 0.106 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.340 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.340 inches

Distance From Mounting Shoulder To Front Face:

0.310 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping



Gold single mating (end single contact grouping
Insert Material:	
	nylene single mating end
	reatment Specification:
	grade c, class 2 military specification single treatment response single mating end single contact grouping
Terminal Type:	grade c, class 2 military specification single treatment response single mating end single contact grouping
	nd single contact grouping
Contact Material S	
	federal specification single material response single mating end single contact grouping
Shell Material:	
Steel	
	rification
Shell Material Spec	
Included Contact G	8, cond a federal specification single material response
	single contact grouping
Included Contact T	a mating end single contact grouping
Precious Material	
Contact surface gold	
Precious Material	
0.005 gold grains, t	
Precious Material:	
Gold	
Thread Series Desi	ignator.
Uns	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Sta	andard):
Mil-g-45204 spec.	