## NSN 5935-00-468-2519

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-468-2519

**Body Style:** 

Straight shape

**Overall Length:** 

Between 2.073 inches and 2.103 inches

**Overall Height:** 

0.663 inches

**Overall Width:** 

Between 0.479 inches and 0.509 inches

**Environmental Protection:** 

Vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

**Distance Between Mounting Facility Centers:** 

Between 1.847 inches and 1.857 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

25 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Surface Treatment:** 

Cadmium

**Shell Surface Treatment Specification:** 

Qq-p-416, type 2, class 2 federal specification single treatment response

**Insert Material Specification:** 

Mil-p-19833, type gdi-30f military specification single material response single mating end or mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

25 single mating end single contact grouping

## NSN 5935-00-468-2519

Mil-std (military Standard):

Mil-p-19833 spec.

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-24308/2 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0