Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-468-3474

# Thread Class: 2a Thread Direction: Right-hand Body Style: Straight shape, external coupling

**Overall Length:** 

1.340 inches

**Overall Height:** 

1.258 inches

**Overall Width:** 

1.258 inches

**Environmental Protection:** 

Moisture resistant and salt water resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.116 inches and 0.126 inches

### Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.964 inches and 0.974 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.964 inches and 0.974 inches

#### **Distance From Mounting Shoulder To Front Face:**

0.775 inches

#### Threaded Device Type:

Back shell

#### Mating End Quantity:

1

#### Contact Removability:

Removable single mating end single contact grouping

#### **Polarization Method:**

Key, multiple key groove

#### **Insert Position In Deg:**

255.0 and 220.0 and 145.0 and 95.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet pin

## Thready Qty Per Inch (tpi):

28

# Thread Size:

1.000 inches

# **Terminal Location:**

Back single mating end single contact grouping

# NSN 5935-00-468-3474

Electrical Receptacle Connector - Page 2 of 2



Contact Materia	
	ngle mating end single contact grouping
Contact Surfac	
Gold single mat	ing end single contact grouping
Contact Surfac	e Treatment Specification:
Mil-g-45204, ty	pe 1, cl 2 military specification single treatment response single mating end single contact grouping
Terminal Type:	
Crimp single ma	ating end single contact grouping
Shell Material:	
Aluminum alloy	6061
Shell Surface T	Freatment:
Chromium	
Shell Material S	Specification:
Qq-a-367, t6 fec	deral specification single material response
Included Conta	act Quantity:
27 single mating	g end single contact grouping
Included Conta	act Type:
Round socket si	ingle mating end single contact grouping
Precious Mater	rial And Location:
Contact surface	is gold
Precious Mater	rial And Weight:
0.027 gold grain	ns, troy
Precious Mater	rial:
Gold	
Thread Series	Designator:
Un	
Shelf Life:	
N/a	
Unit Of Measur	re:
Demilitarizatio	n:
No	
Fiig:	
A039b0	
Mil-std (military	y Standard):
Mil-g-45204 spe	ЭС.