Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-468-3902

# Thread Class:

2a

**Thread Direction:** 

Right-hand

# **Body Style:**

Straight shape, internal coupling

# **Overall Length:**

1.100 inches

### **Overall Diameter:**

1.350 inches

### **Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

# Threaded Device Type:

Back shell

### Mating End Quantity:

1

### Contact Removability:

Removable single mating end single contact grouping

### Polarization Method:

Keyway or multiple keyway

# **Insert Position In Deg:**

92.0 and 152.0 and 222.0 and 342.0

#### Shell Type:

Solid

# **Connector Locking Method:**

Bayonet latch

# Thready Qty Per Inch (tpi):

28

# Thread Size:

1.000 inches

#### **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 2 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

# Shell Material:

Aluminum alloy 6061

# NSN 5935-00-468-3902

Electrical Plug Connector - Page 2 of 2



**Shell Surface Treatment:** Chromium **Shell Material Specification:** Qq-a-367, t6 federal specification single material response **Included Contact Quantity:** 27 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.027 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Un Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.