

View Online at <https://aerobasegroup.com/nsn/5935-00-468-5872>

Body Style:

Straight shape, internal coupling

Overall Length:

Between 1.320 inches and 1.360 inches

Overall Diameter:

Between 0.480 inches and 0.520 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Mating End Quantity:

2

Contact Position Arrangement Style:

Bnc all mating ends

Contact Removability:

Removable all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

1500.0 all mating ends all contact groupings

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

120.0 and 240.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin and bayonet latch

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and copper all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene all mating ends

Shell Material:

Copper alloy 360

Shell Surface Treatment:

Gold

Shell Material Specification:

Qq-b-626, comp 360 federal specification single material response

Included Contact Quantity:

1 2nd mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0