

View Online at <https://aerobasegroup.com/nsn/5935-00-468-5872>

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

Between 1.320 inches and 1.360 inches

**Overall Diameter:**

Between 0.480 inches and 0.520 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Bnc all mating ends

**Contact Removability:**

Removable all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

1500.0 all mating ends all contact groupings

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

120.0 and 240.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin and bayonet latch

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends all contact groupings

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:**

Gold all mating ends all contact groupings and copper all mating ends all contact groupings

**Insert Material:**

Plastic tetrafluoroethylene all mating ends

**Shell Material:**

Copper alloy 360

**Shell Surface Treatment:**

Gold

**Shell Material Specification:**

Qq-b-626, comp 360 federal specification single material response

**Included Contact Quantity:**

1 2nd mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0