Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-469-2759

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight edge type w/mounting flange
Overall Length:
3.203 inches
Overall Height:
Between 0.676 inches and 0.816 inches
Overall Width:
0.340 inches
Distance Between Mounting Facility Centers:
2.945 inches
Board Accommodated Length:
2.500 inches single board
Threaded Device Type:
Mounting hole
Board Accommodated Width:
0.062 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Bridged contacts inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Connector Locking Method:
Friction
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end



Contact Surface Treatment Specification: Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Insert Material Specification:** Mil-p-19833, ty gdi-30f military specification single material response single mating end **Included Contact Quantity:** 15 single mating end single contact grouping Included Contact Type: Leaf spring single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.015 gold grains, troy and 0.015 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.