# NSN 5935-00-470-0304

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-470-0304

# **Body Style:**

Straight shape, internal coupling w/strain relief

## **Body Length:**

2.156 inches

# **Overall Diameter:**

1.062 inches

## **Environmental Protection:**

Pressure proof and heat resistant and vibration resistant

## **Cable Entrance Diameter:**

0.312 inches

## Mating End Quantity:

1

### **Contact Position Arrangement Style:**

12-p single mating end

# Contact Removability:

Nonremovable single mating end single contact grouping

# Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

## Polarization Method:

Keyway or multiple keyway

# Insert Position In Deg:

0.0

#### Shell Type:

Solid

## **Connector Locking Method:**

Spring friction

## **Connector Cable Strain Relief Method:**

Cable clamp

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

# **Terminal Type:**

Solder well single mating end single contact grouping

# Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Cadmium

# Included Contact Quantity:

12 single mating end single contact grouping

# NSN 5935-00-470-0304

Electrical Plug Connector - Page 2 of 2



Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surface gold and contact surface silver **Precious Material And Weight:** 0.012 gold grains, troy and 0.012 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0