NSN 5935-00-470-5063

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-470-5063
Body Style:
Straight shape, external coupling strain relief
Overall Height:
1.567 inches
Overall Width:
1.567 inches
Body Length:
2.125 inches
Environmental Protection:
Heat resistant and moisture proof and vibration resistant
Unthreaded Mounting Hole Diameter:
0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.255 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.255 inches
Cable Entrance Diameter:
0.955 inches
Distance From Mounting Shoulder To Front Face:
0.728 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
22-12 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
41.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Cable clamp
Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-00-470-5063

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Rubber synthetic single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Shell Material Specification:
Qq-a-367, comp 6061, t6 federal specification single material response
Included Contact Quantity:
12 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.070 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: