Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-470-5063

Body Style:

Straight shape, external coupling strain relief

Overall Height:

1.567 inches

Overall Width:

1.567 inches

Body Length:

2.125 inches

Environmental Protection:

Heat resistant and moisture proof and vibration resistant

Unthreaded Mounting Hole Diameter:

0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.255 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.255 inches

Cable Entrance Diameter:

0.955 inches

Distance From Mounting Shoulder To Front Face:

0.728 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

22-12 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

41.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping



Contact Surface	e Treatment:
Gold single matir	ng end single contact grouping
Insert Material:	
Rubber synthetic	single mating end
Contact Surface	e Treatment Specification:
Mil-g-45204, type	e 2, class 2 military specification single treatment response single mating end single contact grouping
Terminal Type:	
Crimp single mat	ting end single contact grouping
Shell Material:	
Aluminum alloy 6	5061
Shell Surface T	reatment:
Anodize	
Shell Surface T	reatment Specification:
Mil-a-8625 milita	ry specification single treatment response
Shell Material S	pecification:
Qq-a-367, comp	6061, t6 federal specification single material response
Included Contac	ct Quantity:
12 single mating	end single contact grouping
Included Contac	ct Type:
Round socket sir	ngle mating end single contact grouping
Precious Materi	al And Location:
Contact surfaces	s gold
Precious Materi	al And Weight:
0.070 gold grains	s, troy
Precious Materi	al:
Gold	
Shelf Life:	
N/a	
Unit Of Measure	e:
Demilitarization	:
No	
Fiig:	
A039b0	
Mil-std (military	Standard):
Mil-g-45204 spec	2.