

View Online at https://aerobasegroup.com/nsn/5935-00-470-7367

# Body Style:

Straight shape

## **Overall Length:**

Between 3.290 inches and 3.310 inches

# Overall Height:

0.565 inches

#### **Overall Width:**

Between 0.240 inches and 0.260 inches

#### **Unthreaded Mounting Hole Diameter:**

Between 0.110 inches and 0.130 inches

#### Distance Between Mounting Facility Centers:

Between 3.040 inches and 3.060 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

## Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

## Polarization Method:

Guide pin/socket

**Terminal Location:** 

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

## Insert Material:

Plastic diallyl phthalate single mating end

## Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Solder well single mating end single contact grouping

## **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

## Insert Material Specification:

Mil-p-19833 military specification single material response single mating end

#### **Included Contact Quantity:**

54 single mating end single contact grouping

#### Included Contact Type:

Round socket single mating end single contact grouping



Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.054 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: --

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.