## NSN 5935-00-470-8947



Electrical Plug Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-470-8947 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.230 inches **Overall Diameter:** 1.777 inches **Environmental Protection:** Heat resistant and moisture resistant and oil tight and salt water resistant and vibration resistant **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 24-61 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 90.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch Thread Length: 0.290 inches **Thread Size:** 1.438 inches **Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic single mating end

## **NSN 5935-00-470-8947**Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
61 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.061 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
81349-mil-c-83723/14 government specification
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A039b0