NSN 5935-00-470-9411

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-470-9411	
Body Style:	
Straight shape, external coupling strain relief	
Overall Height:	
1.438 inches	
Overall Width:	
1.438 inches	
Body Length:	
1.125 inches	
Environmental Protection:	
Watertight	
Unthreaded Mounting Hole Diameter:	
0.120 inches	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
1.187 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
1.187 inches	
Distance From Mounting Shoulder To Front Face:	
0.531 inches	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
3719p single mating end	
Contact Removability:	
Nonremovable single mating end all contact groupings	
Contact Maximum Current Rating In Amps:	
7.5 single mating end 2nd contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
75.0	
Shell Type:	
Solid	
Connector Locking Method:	
Spring friction	
Connector Cable Strain Relief Method:	

_

Cable clamp

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

NSN 5935-00-470-9411

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
6 single mating end 1st contact grouping
Included Contact Type:
Round pin single mating end 2nd contact grouping
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material And Weight:
$0.019 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.019 \ \text{silver grains}, \ \text{troy}$
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0