NSN 5935-00-470-9429

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-470-9429

view Online at https://aerobasegroup.com/nsn/5935-00-470-9429
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
2.219 inches
Overall Diameter:
1.359 inches
Environmental Protection:
Heat resistant and pressure proof and vibration resistant
Cable Entrance Diameter:
0.562 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
27-5 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
25.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Spring friction
Connector Cable Strain Relief Method:
Cable clamp
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium

Included Contact Quantity:

19 single mating end single contact grouping

NSN 5935-00-470-9429

Electrical Plug Connector - Page 2 of 2



Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material And Weight:

0.019 gold grains, troy and 0.019 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0