NSN 5935-00-471-2075

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-471-2075 **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 1.709 inches **Overall Height:** 1.703 inches **Overall Width:** 1.703 inches **Unthreaded Mounting Hole Diameter:** Between 0.142 inches and 0.152 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.375 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:** 1.375 inches **Distance From Mounting Shoulder To Front Face:** Between 0.589 inches and 0.599 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 24-61 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 2100.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 180.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-00-471-2075

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Chromate
Included Contact Quantity:
61 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.061 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0