

View Online at <https://aerobasegroup.com/nsn/5935-00-471-4531>

Body Style:

Straight shape, internal coupling

Overall Length:

Between 1.320 inches and 1.360 inches

Overall Diameter:

Between 0.480 inches and 0.520 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Mating End Quantity:

2

Contact Position Arrangement Style:

Bnc all mating ends

Contact Removability:

Removable all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends all contact groupings

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

120.0 and 240.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin and bayonet latch

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings and copper all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and copper all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene all mating ends

Shell Surface Treatment:

Silver

Shell Surface Treatment Specification:

Qq-s-365 federal specification single treatment response

Insert Material Specification:

Qq-s-265, grade a federal specification single material response all mating ends

Included Contact Quantity:

1 2nd mating end all contact groupings

Precious Material And Location:

Contact surfaces gold and body surfaces silver

Precious Material And Weight:

0.010 gold grains, troy and 0.200 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0