NSN 5935-00-471-6183

Electrical Receptacle Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-00-471-6183 |
|---|
| Body Style: |
| Straight shape, external coupling w/backshell |
| Overall Length: |
| 1.278 inches |
| Overall Height: |
| 1.208 inches |
| Overall Width: |
| 1.208 inches |
| Environmental Protection: |
| Moisture resistant and salt water resistant and vibration resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.120 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 0.906 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.906 inches |
| Distance From Mounting Shoulder To Front Face: |
| 0.526 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 1912p single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 600.0 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 235.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Ball |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Terminal Type: |

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

NSN 5935-00-471-6183 Electrical Receptacle Connector - Page 2 of 2



| Shell Surface Treatment: |
|--|
| Cadmium |
| ncluded Contact Quantity: |
| 12 single mating end single contact grouping |
| ncluded Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surface gold |
| Precious Material And Weight: |
| 0.012 gold grains, troy |
| Precious Material: |
| Gold |
| Test Data Document: |
| 31349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 31349-mil-c-26482 government specification |
| Shelf Life: |
| N/a |
| Jnit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| A039b0 |
| |
| |