

View Online at <https://aerobasegroup.com/nsn/5935-00-471-7024>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape threaded

Overall Diameter:

2.079 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Distance From Mounting Shoulder To Front Face:

0.754 inches

Mounting Facility Thickness:

0.219 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

24-61 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

97.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thready Qty Per Inch (tpi):

18

Thread Size:

1.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Rubber fluorosilicone class fq single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Included Contact Quantity:

61 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.061 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.