Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-471-7312

# **Body Style:**

Straight shape, external coupling

# **Overall Height:**

1.141 inches

# **Overall Width:**

1.141 inches

### **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

#### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

# Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.901 inches and 0.911 inches

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.901 inches and 0.911 inches

# Distance From Mounting Shoulder To Front Face:

Between 0.457 inches and 0.467 inches

# Mating End Quantity:

1

# **Contact Position Arrangement Style:**

14-19 single mating end

# **Contact Removability:**

Removable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

75.0

# Shell Type:

Solid

# **Connector Locking Method:**

Bayonet pin

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Insert Material:

Rubber fluorosilicone class fq single mating end

# Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Crimp single mating end single contact grouping

# NSN 5935-00-471-7312

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Included Contact Quantity:
19 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.019 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.