

View Online at <https://aerobasegroup.com/nsn/5935-00-471-9987>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Right angle type

Overall Length:

1.350 inches

Overall Height:

0.509 inches

Overall Width:

0.250 inches

Environmental Protection:

Vibration resistant and shock resistant and salt water resistant and humidity resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

1.100 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Operating Temperature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Glass and plastic phenolic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14g, ty mfh military specification all material responses single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

10 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Jackscrew type-female and location-right hand and jackscrew type-male and location-left hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.