NSN 5935-00-473-3138

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-473-3138 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, round **Overall Height:** 0.625 inches Diameter: 0.312 inches **Overall Diameter:** 0.500 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration resistant **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thread Length: 0.187 inches Thready Qty Per Inch (tpi): **Thread Size:** 0.313 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:**

mocre material.

Ceramic single mating end

NSN 5935-00-473-3138

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Gold
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact and body surfaces gold
Precious Material And Weight:
0.105 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0