## NSN 5935-00-476-4618

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-476-4618

**Body Style:** 

Straight shape

**Overall Length:** 

Between 2.714 inches and 2.744 inches

**Overall Height:** 

Between 0.479 inches and 0.509 inches

**Overall Width:** 

Between 0.478 inches and 0.510 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

**Distance Between Mounting Facility Centers:** 

Between 2.495 inches and 2.505 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

37 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

**Shell Material:** 

Steel

**Shell Surface Treatment:** 

Cadmium

**Shell Surface Treatment Specification:** 

Qq-p-416, type 2, class 2 federal specification single treatment response

**Insert Material Specification:** 

Mil-m-19833, type gdi-30f military specification single material response single mating end

## NSN 5935-00-476-4618

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:**

37 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.037 gold grains, troy

**Precious Material:** 

Gold

Fsc Application Data (non-core):

Connectors, electrical

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.