

View Online at <https://aerobasegroup.com/nsn/5935-00-476-6322>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.840 inches

Overall Diameter:

0.810 inches

Cable Entrance Diameter:

0.260 inches

Distance From Mounting Shoulder To Front Face:

Between 0.912 inches and 0.940 inches

Mounting Facility Thickness:

Between 0.080 inches and 0.250 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

N single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

11.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thread Length:

0.625 inches

Thread Size:

0.625 inches

Contact Material:

Copper alloy single mating end single contact grouping

Insert Material:

Copper alloy single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0