Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-477-0966

Thread Class:
2g
Thread Pitch Diameters:
+1.989/+2.000 inches
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
5.719 inches
Overall Diameter:
2.484 inches
Environmental Protection:
Humidity resistant and moisture resistant and corrosion resistant and shock resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
16-22 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
135.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1250.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Connector Cable Strain Relief Method:
Cord protector
Thready Qty Per Inch (tpi):
4
Thread Size:
2.000 inches



Terminal Location: Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Rubber synthetic single mating end **Criticality Code Justification:** Feat **Terminal Type:** Solder well single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 4 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round Included Contact Type: Round socket single mating end single contact grouping **Special Features:** 1.000 in. Min and 1.125 in. Maximum diameter cable opening **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Special acme Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0