Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-477-1147

## **Thread Class:** 2a **Thread Direction: Right-hand Body Style:** Straight shape, external coupling **Overall Length:** 0.594 inches **Overall Diameter:** 0.250 inches **Environmental Protection:** Moisture resistant and salt water resistant **Distance From Mounting Shoulder To Front Face:** 0.274 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Smb single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Detent Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic polychlorotrifluoroethylene single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 1, cl 2, grade c military specification 1st treatment response single mating end single contact grouping and mil-c-14550, cl

4 military specification 2nd treatment response single mating end single contact grouping



## **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-b-626, comp 22 federal specification single material response single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** Gold and copper **Shell Surface Treatment Specification:** Mil-g-45204, type 1, cl 2, grade c military specification 1st treatment response and mil-c-14550, cl 4 military specification 2nd treatment response **Shell Material Specification:** Qq-b-626, comp 22 federal specification single material response **Insert Material Specification:** Mil-p-19464 military specification single material response single mating end **Included Contact Quantity:** 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Coaxial pin single mating end single contact grouping **Precious Material And Location:** Contact and shell surfaces gold **Precious Material And Weight:** 0.105 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.