NSN 5935-00-477-7684

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-477-7684 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.818 inches **Overall Height:** Between 1.422 inches and 1.454 inches **Overall Width:** Between 1.422 inches and 1.454 inches **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches **Distance From Mounting Shoulder To Front Face:** Between 0.317 inches and 0.322 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 330.0 Shell Type: **Connector Locking Method:** Bayonet pin **Thread Length:** 0.219 inches Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.158 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-00-477-7684

Electrical Receptacle Connector - Page 2 of 2



Contact Material: Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic silicone mineral filled single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and nickel **Included Contact Quantity:** 65 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.065 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Uns Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No Fiig: A039b0