

View Online at https://aerobasegroup.com/nsn/5935-00-477-8499

Body Style:

Straight edge type

Overall Length:

Between 4.282 inches and 4.352 inches

Overall Height:

Between 0.921 inches and 0.931 inches

Overall Width:

Between 0.335 inches and 0.345 inches

Unthreaded Mounting Hole Diameter:

Between 0.123 inches and 0.133 inches

Distance Between Mounting Facility Centers:

Between 4.021 inches and 4.041 inches

Board Accommodated Length:

3.586 inches single board and 3.596 inches single board

Board Accommodated Width:

0.063 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end



Included Contact Quantity:

22 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.022 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.