# NSN 5935-00-478-3055

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-478-3055

**Body Style:** 

Rectangular shape, angle

**Overall Length:** 

Between 2.073 inches and 2.103 inches

**Overall Height:** 

0.584 inches

**Overall Width:** 

0.750 inches

#### **Environmental Protection:**

Moisture resistant and vibration resistant and shock resistant and corrosion resistant and salt spray proof

#### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

#### **Distance Between Mounting Facility Centers:**

Between 1.847 inches and 1.857 inches

#### **Mating End Quantity:**

1

# **Contact Position Arrangement Style:**

25 single mating end

# **Contact Removability:**

Removable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

#### **Polarization Method:**

Mating end

# Shell Type:

Solid

# **Connector Locking Method:**

Friction

#### **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 150.0 degrees celsius

# **Terminal Location:**

Side single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

# **Insert Material:**

Plastic diallyl phthalate single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping

# **Terminal Type:**

Printed circuit single mating end single contact grouping

# NSN 5935-00-478-3055

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Steel
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type ii, class 2 federal specification all treatment responses
Shell Material Specification:
Qq-s-698 federal specification single material response
Insert Material Specification:
Mil-m-19833, ty gdi-30f military specification single material response single mating end
Included Contact Quantity:
25 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.025 gold grains, troy and 0.025 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.