

View Online at <https://aerobasegroup.com/nsn/5935-00-478-5279>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.375 inches

Bushing Diameter:

0.437 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.562 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.562 inches

Distance From Mounting Shoulder To Front Face:

0.687 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thread Length:

0.187 inches

Thread Size:

0.437 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Pin single mating end single contact grouping

Shell Material:

Copper

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0