## NSN 5935-00-479-8036

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-479-8036

view Orilline at https://derobasegroup.com/his//0000-470-0000
Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.375 inches
Overall Diameter:
1.537 inches
Environmental Protection:
Vibration resistant and moisture resistant and shock resistant
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
55 number 20 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
80.0 and 118.0 and 230.0 and 312.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
1.312 inches and 1.438 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping and nickel single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping and rhodium single mating end single contact grouping
Insert Material:

Rubber single mating end

## NSN 5935-00-479-8036

A039b0

Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Steel
Included Contact Quantity:
55 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver and contact surfaces rhodium
Precious Material And Weight:
0.055 silver grains, troy and 0.055 rhodium grains, troy
Precious Material:
Silver and rhodium
Test Data Document:
11293-73-266111 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig: