Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-479-8071

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling strain relief
Overall Length:
1.906 inches
Overall Height:
1.281 inches
Overall Width:
1.281 inches
Environmental Protection:
Moisture resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.968 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.968 inches
Distance From Mounting Shoulder To Front Face:
0.750 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
16s-6 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:

Solid



Connector Locking Method: Externally threaded shell **Connector Cable Strain Relief Method:** Compression nut **Thread Length:** 0.625 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 1.000 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 3 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.003 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0